



FOOD111

TARY SCHOOLS

215 S.E. 6th Ave.
HILLSBORO, OR 97123

MATERIAL SAFETY DATA SHEET

FS 0016

Page 3 of 3 04 MAY 1990 Product Name: SERCO OVEN AND GRILL
MS Number: 27730 MATERIAL SAFETY DATA SHEET MS Number: 27730

SECTION V REACTIVITY DATA is continued from the previous page.

Polymerization Polymerization will not occur.

Avoid: NONE KNOWN.

SECTION VI HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Inhalation: YES

Skin: YES

Ingestion: NO

Eye: NO

ADDITIONAL INFORMATION

MS: ACUTE AND CHRONIC HEALTH HAZARD

CARCINOGENICITY

MS: NO MSCT-NO MSCT-NO

ACUTE AND CHRONIC HEALTH HAZARD

ACUTE

INHALATION: EXCESSIVE INHALATION OF VAPORS CAN BE HARMFUL AND MAY CAUSE HEADACHE, DIZZINESS, APTAXIA, ANESTHETIC EFFECTS AND POSSIBLE UNCONSCIOUSNESS.

SKIN: CAUSTIC; MAY CAUSE BURNS.

EYES: CAUSTIC; MAY CAUSE BURNS.

INGESTION: POSSIBLE CHEMICAL PNEUMONITIS IF ASPIRATED INTO LUNGS. CAUSTIC; MAY CAUSE BURNS.

CHRONIC: LAB ANIMALS HAVE EXPERIENCED ANEMIA, DYSPNOEA, EDHEMIA, LUNG, BLADDER AND KIDNEY TISSUE DAMAGE. MAY CAUSE BURNS, DERMATITIS, RESPIRATORY AND CENTRAL NERVOUS DISORDERS IN HUMAN.

SECTION VI HEALTH HAZARD DATA is continued on the next page.

Page 3

Page 2 of 3 04 MAY 1990 Product Name: SERCO OVEN AND GRILL
MS Number: 27730 MATERIAL SAFETY DATA SHEET MS Number: 27730

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS continued from the previous page.

Vapor Pressure (mm Hg): 2.5 DEC 75 DEC 75 (ASBOSOL) - MAX. 40

Vapor Density (Air = 1): N/A

Evaporation Rate: N/A

Solubility/Water: SOLUBLE

% Volatile by Volume: N/A

APPEARANCE AND ODOR

TAN FOAMY GEL WITH LEMON FRAGRANCE.

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point: N/A

Auto-Ignition: N/A

REL: N/A

UEL: N/A

HAZARD CLASSIFICATION

Flammable: 1 Health: 2 Reactivity: 1 Special: 0

EXTINGUISHING MEDIA

FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER. PRODUCT IS NON-FLAMMABLE.

SPECIAL FIRE FIGHTING PROCEDURES

SELF CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARDS

DO NOT EXPOSE ADDITIVES TO TEMPERATURES ABOVE 150 DEG F OR THE CONTAINERS MAY RUPTURE.

SECTION V REACTIVITY DATA

Reactivity (Product) is stable.

Avoid: OPEN FLAME, WELDING ARCS, HEAT.

INCOMPATIBILITY (Substance to Avoid)

STRONG ACIDS AND OXIDIZERS.

HAZARDOUS DISCOMPOSITION OR BY-PRODUCTS

CARBON MONOXIDE, CARBON DIOXIDE.

SECTION V REACTIVITY DATA is continued on the next page.

Page 2

Page 1 of 3 04 MAY 1990 Product Name: SERCO OVEN AND GRILL
MS Number: 27730 MATERIAL SAFETY DATA SHEET MS Number: 27730

SECTION I IDENTIFICATION

Chemical Name: SERCO OVEN AND GRILL CLEANER AERO SOL

MS Number: 27730

SECTION II SUPPLIER INFORMATION

Supplier Name: AEROSOL OVEN CLEANER

Supplier Address: 751 TERMINAL STREET

Supplier City: SAN ANGELES

Supplier State: CA

Supplier Zip: 95412

Supplier Phone: 213-422-4131

Supplier Fax: 213-422-4131

Supplier Email: 213-422-4131

Date Issued: 04 12 76

Revised:

SECTION III INGREDIENT INFORMATION

INGREDIENTS

BUTANE

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

1% CAS 6: 76-98-6 P.E. 0.5% N/A TV ACQ: 1%

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS continued on the next page.

Page 1

SECTION VI HEALTH HAZARD DATA is continued from the previous page.

***** MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE *****

MAY AGGRAVATE EXISTING EYE, SKIN, OR UPPER RESPIRATORY CONDITIONS.

***** EMERGENCY AND FIRST AID PROCEDURES *****

EYE: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATED, SEE PHYSICIAN.

SKIN: WASH WITH SOAP AND WATER. IF IRRITATED, SEE PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NECESSARY. GET MEDICAL AID.

INGESTION: GIVE MILK OR PLENTY OF WATER. DO NOT INDUCE VOMITING. CALL PHYSICIAN.

***** PRECAUTIONS FOR SAFE HANDLING AND USE *****

DOT Classification: NOT DOT REGULATED (ORM-D)

***** STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED *****

ABSORB WITH SUITABLE MEDIUM. INCINERATE OR LANDFILL ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS. DILUTE WITH WATER, ABSORB WITH CLOTH OR NEUTRALIZE WITH DILUTE ACID AND FLUSH TO SEWER.

***** WASTE DISPOSAL METHOD *****

AEROSOL CAN, WHEN VENTED TO ATMOSPHERIC PRESSURE THROUGH NORMAL USE, POSSES NO DISPOSAL HAZARD.

***** PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE *****

DO NOT PUNCTURE OR INCINERATE CONTAINERS. DO NOT STORE AT TEMPERATURES ABOVE 150 DEG F.

***** OTHER PRECAUTIONS *****

AVOID FOOD CONTAMINATION. KEEP OUT OF REACH OF CHILDREN. DO NOT USE ON ALUMINUM. AVOID BREATHING VAPORS.

***** SECTION VII CONTROL MEASURES *****

SECTION VII CONTROL MEASURES is continued on the next page.

SECTION VII CONTROL MEASURES is continued from the previous page.

***** RESPIRATORY PROTECTION *****

IF VAPOR CONCENTRATION EXCEEDS TLV, USE RESPIRATOR APPROVED BY MSHA IN POSITIVE PRESSURE MODE.

***** VENTILATION *****

Local Exhaust: ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATION BELOW TLV.

Special Exhaust: N/I
Mechanical Exhaust: N/I

***** OTHER PROTECTION *****

Gloves: RUBBER GLOVES.
Eye Protection: SAFETY GLASSES RECOMMENDED.

***** CLOTHING *****

NO SPECIAL CLOTHING REQUIRED.

***** WORK/HYGIENE PRACTICES *****

WASH WITH SOAP AND WATER BEFORE HANDLING FOOD. REMOVE CONTAMINATED CLOTHING.

***** DISCLAIMER *****

While E.S. Rykoff & Co. believes that the data contained herein are factual and the opinions expressed are based on recognized safety practices, the data are not to be taken as a warranty or representation for which E.S. Rykoff & Co. assumes legal responsibility. They are offered solely for your consideration, investigation and verification.

THIS IS THE END OF THE MSDS Id #27730
Page 5