



PNT103

ARY SCHOOLS

215 S.E. 6th Ave.
HILLSBORO, OR 97123

MATERIAL SAFETY DATA SHEET IN 0027

SECTION I

PRODUCT CODE NUMBER _____ TLV _____
MANUFACTURER'S NAME Partra Containers, Inc. EMERGENCY INFORMATION (714) 946-3871
MANUFACTURER'S ADDRESS 430 S. 11th Avenue, Upland, CA 91786
PRODUCT Everyday Spray Paint - Hot Red Primer COMMON NAME _____
GENERIC NAME _____ CHEMICAL NAME _____
CHEMICAL FAMILY _____ DOT PROPER SHIPPING NAME _____
WARNING STATEMENTS _____

SECTION II - INGREDIENTS

	C.A.S. #	%	TLV
Aliphatic Hydrocarbons	64742-89-8	4-8	300
Acetone	67-64-1	10-15	750
Xylene	1330-20-7	30-35	100

IN FLAM, FIRE & EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors or other ignition sources at locations distant from material handling point.

* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE _____ VAPOR PRESSURE _____
VAPOR DENSITY Heavier than air. SOLUBILITY IN WATER _____
SPECIFIC GRAVITY _____ PERCENT VOLATILE: _____
EVAPORATION RATE Slower than Ether. APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE -4°F EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Foam
FIRE FIGHTING PROCEDURES Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
UNUSUAL FIRE AND EXPLOSION HAZARDS See in Section II. CLASSIFICATION _____

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT _____
SKIN CONTACT _____
INHALATION If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
INGESTION Do not induce vomiting, keep person warm, quiet and get medical attention.

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS EFFECTS OF OVEREXPOSURE: Drowsiness or dizziness.

CHRONIC EFFECTS: _____

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable.

INCOMPATIBILITY (Materials to Avoid): _____

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce poisonous gas. Contains chlorinated solvent.

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Remove sources of ignition. Cover with absorbent inert material. Sweep up and store in a waste disposal container.

WASTE DISPOSAL METHOD: Waste may be incinerated in accordance with Federal and Local pollution laws.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a respirator approved by the U.S. Bureau of Mines for Organic Vapors.

VENTILATION: Local Exhaust. Maintain level below .25 lcl.

PROTECTIVE GLOVES: Yes.

EYE PROTECTION: Yes.

OTHER PROTECTIVE EQUIPMENT: None.

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Store in well ventilated areas away from heat and all ignition source.

OTHER PRECAUTIONS: Use explosion proof equipment.

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: August 29, 1984