

IN 0010

215 S.E. 61st Ave.
HILLSBORO, OR 97123

PRODUCT CODE NUMBER: _____ *TLV _____
MANUFACTURER'S NAME The Testor Corporation EMERGENCY INFORMATION (815) 962-6654
MANUFACTURER'S ADDRESS 620 Buckbee Street, Rockford, IL 61108
PRODUCT Cement For Wood Models #3505 & 3506 COMMON NAME _____
GENERIC NAME _____ CHEMICAL NAME _____
CHEMICAL FAMILY _____ DOT PROPER SHIPPING NAME _____
WARNING STATEMENTS _____

	C.A.S. #	% by wt.	TLV
Nitrocellulose	9004-70-0	15	Not Applicable
Diethyl Phthalate	117-81-7	<5	5 mg./cu. Meter
Toluol (Toluene)	108-88-3	25	TLV/TWA 100 ppm PEL/TWA 200 ppm
Isopropyl Acetate	108-21-4	30	TLV/TWA 250 ppm PEL/TWA 250 ppm
n-Butyl Acetate	123-86-4	<5	TLV/TWA 150 ppm PEL/TWA 150 ppm
Acetone	67-64-1	<5	TLV/TWA 750 ppm PEL/TWA 1000 ppm
Hexane	110-54-3	20	TLV/TWA 500 ppm PEL/TWA 500 ppm
Isopropyl Alcohol	67-63-0	5	TLV/TWA 400 ppm PEL/TWA 400 ppm
Oil of Mustard (Allyl Isothiocyanate)	57-06-7	<.5	Unknown

Threshold limit value set by (a) OSHA, (b) ACGIH, (c) See Section III, (d) Other, (nc) Not Established (Units are in ppm unless otherwise specified)

UNITED STATES GOVERNMENT PRINTING OFFICE: 1967 O 344-101

APPROXIMATE BOILING RANGE. <u>156°</u>	VAPOR PRESSURE: <u>Of Volatile Portion: 59 mm. Hg 20°C</u> (Calc)
VAPOR DENSITY: <u>Of Volatile Portion: (Air-1): 3.15</u> (Calc)	SOLUBILITY IN WATER: <u>Negligible</u>
SPECIFIC GRAVITY. <u>.885</u>	PERCENT VOLATILE: <u>By volume of product: 91.4 (Calc)</u>
EVAPORATION RATE <u>(BU.AC=1): 3.94</u>	APPROXIMATE BULK DENSITY: _____

FLASH POINT RANGE: 18°F TOC EXTINGUISHING MEDIA: Mechanical foam, dry chemical, water fog or CO₂
FIRE FIGHTING PROCEDURES: A straight stream of water could spread fire. DOT FLAMMABILITY CLASSIFICATION: _____
UNUSUAL FIRE AND EXPLOSION HAZARDS: Toxic gases are evolved when nitrocellulose burns. Avoid unnecessary exposures.

water

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eyelids open.

SKIN CONTACT: Wash immediately with mild soap and water.

INHALATION: Remove to fresh air. Use artificial respiration if needed.

INGESTION: Do not induce vomiting. Call physician at once. If vomiting occurs, keep head below hips to prevent aspiration into lungs.

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS EFFECTS OF OVEREXPOSURE: Skin Contact: Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis. Eye Contact: Liquid splashes and high vapor concentrations cause irritation. Liquid may result in corneal injury which heals slowly.

CHRONIC EFFECTS Breathing: Concentrations above the TLV may be irritative and cause dizziness, headache, nausea, vomiting and possibly narcosis. Swallowing: May result in vomiting. Aspiration (breathing) of vomitus into lungs must be avoided as even small quantities in the lungs may result in chemical pneumonitis and edema.

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable. Avoid heat, sparks, flame and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong alkalis and strong oxidizing agents. Toxic gases are evolved when nitrocellulose burns.

HAZARDOUS DECOMPOSITION PRODUCTS Carbon Monoxide if burned with insufficient air.

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur. None.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Eliminate all possible ignition sources. Take up with an absorbent material and place in non-leaking container. Seal for proper disposal.

WASTE DISPOSAL METHOD: Do not incinerate closed container. Dispose of in accordance with Local, State, and Federal regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If TLV is exceeded, use self-contained breathing apparatus.

VENTILATION: LOCAL EXHAUST: Preferred. Mechanical (General): Use explosion proof equipment. Special: N/A Other: N/A

PROTECTIVE GLOVES Not needed.

EYE PROTECTION: Safety goggles.

OTHER PROTECTIVE EQUIPMENT: None.

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Read all label cautions. Store away from ignition sources.

OTHER PRECAUTIONS: Handle as extremely flammable liquid.

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: May, 1985