



HILLSBORO ELEMENTARY SCHOOLS

215 S.E. 6th Ave.
HILLSBORO, OR 97123

MATERIAL SAFETY DATA SHEET IN 0059

SECTION I

PRODUCT CODE NUMBER _____ *TLV _____
MANUFACTURER'S NAME Sanford Corporation EMERGENCY INFORMATION 312-547-6650
MANUFACTURER'S ADDRESS 2740 Washington Blvd., Bellwood, IL 60104
PRODUCT Sanford's Rubber Cement COMMON NAME _____
GENERIC NAME _____ CHEMICAL NAME Solvent Adhesive
CHEMICAL FAMILY Mixture DOT PROPER SHIPPING NAME _____
WARNING STATEMENTS _____

SECTION II - INGREDIENTS

	%	TLV
Paints, Preservatives, & Solvents		
Vehicle: Rubber	10-12	Undet
Solvents: Hexane	85-90	50ppm

* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: 152-157 VAPOR PRESSURE: 140
VAPOR DENSITY: 3.0 SOLUBILITY IN WATER: NIL
SPECIFIC GRAVITY: 0.71 PERCENT VOLATILE: 85-90
EVAPORATION RATE: 8.1 APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: 0°F (TCC) EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chem.
FIRE FIGHTING PROCEDURES: Follow guidelines for Class 1/ Group 1 Flammable liquid. DOT FLAMMABILITY CLASSIFICATION: 1el: 1.2 1el: 7.5
UNUSUAL FIRE AND EXPLOSION HAZARDS: Heavier than air vapors.

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: _____

SKIN CONTACT: _____

INHALATION: Remove to fresh air, see Doctor if symptoms persist.

INGESTION: _____

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS Inhalation - Dizziness, headache, nausea.

CHRONIC EFFECTS _____

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable. High heat, open flame.

INCOMPATIBILITY (Materials to Avoid): _____

HAZARDOUS DECOMPOSITION PRODUCTS: _____

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Eliminate all ignition sources, ventilate area, collect on absorbent material.

WASTE DISPOSAL METHOD: As flammable hazardous waste for liquid.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use NIOSH/MSHA air supplied regulator to keep exposure below TLV's

VENTILATION: (Local Exhaust) Recommended

PROTECTIVE GLOVES: _____

EYE PROTECTION: s needed.

OTHER PROTECTIVE EQUIPMENT: _____

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Appropriate storage for flammable liquid.

OTHER PRECAUTIONS: _____

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: _____