

ITEM: 4HFE7 - Ceiling Sealing Paint 13 Oz

PICK REQ: 1458197605

SAFETY DATA SHEET (SDS)

SDS: F4897

This SDS should be attached or kept with the respective product with which it is associated.

#####

SDS - F4897

Associated Items
4HFE7

DATE PRINTED: 2/22/2019

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

1. IDENTIFICATION

PRODUCT NAME: COVRUP 13-OZ 6 PK SPRAY

PRODUCT IDENTIFIER: 3688

RECOMMENDED USE: TOPCOAT/AEROSOLS

REVISION DATE: 2/22/2019

SUPERCEDES DATE: 5/18/2017

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USAMANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:
24 HOUR HOTLINE: 847-367-7700

2. HAZARD IDENTIFICATION

CLASSIFICATION:

SYMBOL(S) OF PRODUCT:
FLAME
EXCLAMATION MARK
HEALTH HAZARD
GAS CYLINDER

SIGNAL WORD: DANGER

POSSIBLE HAZARDS:
35% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN ACUTE TOXICITY.

GHS HAZARD STATEMENTS:

CARCINOGENICITY, CATEGORY 1B:
H350: MAY CAUSE CANCER.COMPRESSED GAS:
H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.EYE IRRITATION, CATEGORY 2:
H319: CAUSES SERIOUS EYE IRRITATION.FLAMMABLE AEROSOL, CATEGORY 1:
H222: EXTREMELY FLAMMABLE AEROSOL.GERM CELL MUTAGENICITY, CATEGORY 1B:
H340: MAY CAUSE GENETIC DEFECTS.STOT, SINGLE EXPOSURE, CATEGORY 3, NE:
H336: MAY CAUSE DROWSINESS OR DIZZINESS.SKIN SENSITIZER, CATEGORY 1:
H317: MAY CAUSE AN ALLERGIC SKIN REACTION.GHS LABEL PRECAUTIONARY STATEMENTS:
P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.P210:
KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING.

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P251: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY.

P264: WASH HANDS THOROUGHLY AFTER HANDLING.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P272:
CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.P280:
WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.P302+P352:
IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

P304+P340:

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

P305+P351+P338:
IF IN EYES:
RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.P308+P313:
IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P321: FOR SPECIFIC TREATMENT SEE LABEL

P333+P313:
IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION.P337+P313:
IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P405: STORE LOCKED UP.

P410+P403: PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE.

P410+P412:
PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C / 122 DEG. F.P501:
DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL, REGIONAL AND NATIONAL REGULATIONS.GHS SDS PRECAUTIONARY STATEMENTS:
P363: WASH CONTAMINATED CLOTHING BEFORE REUSE.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT.%	GHS SYMBOLS RANGE	GHS STATEMENTS
ACETONE	67-64-1	10-25	GHS02-GHS07	H225-319-332-336
NAPHTHA, HYDROTREATED	64742-48-9	10-25	GHS08	H304-340-350
PROPANE	74-98-6	10-25	GHS04	H280
N-BUTANE	106-97-8	2.5-10	GHS04	H280
TITANIUM DIOXIDE	13463-67-7	2.5-10	NOT AVAILABLE	NOT AVAILABLE
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	6846-50-0	0.1-1.0	GHS06	H331
METHYL ETHYL KETOXIME	96-29-7	0.1-1.0	GHS05-GHS06	H302-312-317-318-331

4. FIRST-AID MEASURES

FIRST AID - EYE CONTACT:
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.FIRST AID - SKIN CONTACT:
WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.FIRST AID - INHALATION:
REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION. IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:

ASPIRATION HAZARD:
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED, GET MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA:
ALCOHOL FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOGUNUSUAL FIRE AND EXPLOSION HAZARDS:
FLASH POINT IS LESS THAN 20 DEG. F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED.SUGGESTED FIRE-FIGHTING PROCEDURES:
WATER MUST BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

E-MAILED DEC 07 2023

FOR THE YEAR 1902

RECEIVED DEC 14 1902

SPECIAL FIRE AND EXPLOSION HAZARD (COMBUSTIBLE DUST): NO INFORMATION

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. VENTILATE AREA, ISOLATE SPILLED MATERIAL, AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED ABSORBENT, CONTAINER, AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE

HANDLING:

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. FOLLOW ALL SDS AND LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES, VAPORS, OR MIST. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

STORAGE:

STORE IN A DRY, WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF FLAMMABLE AEROSOLS. KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT, MOISTURE, AND FOREIGN MATERIALS.

ADVICE ON SAFE HANDLING OF COMBUSTIBLE DUST: NO INFORMATION

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CHEMICAL NAME	CAS-NO.	WEIGHT %	LESS THAN
ACETONE	67-64-1	25.0	
NAPHTHA, HYDROTREATED HEAVY	64742-48-9	20.0	
PROPANE	74-98-6	15.0	
N-BUTANE	106-97-8	10.0	
TITANIUM DIOXIDE	13463-67-7	10.0	
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	6846-50-0	1.0	
METHYL ETHYL KETOXIME	96-29-7	1.0	

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
ACETONE	250 PPM	500 PPM	1000 PPM	N.E.
NAPHTHA, HYDROTREATED HEAVY	N.E.	N.E.	N.E.	N.E.
PROPANE	N.E.	N.E.	1000 PPM	N.E.
N-BUTANE	N.E.	1000 PPM	N.E.	N.E.
TITANIUM DIOXIDE	10 MG/M3	N.E.	15 MG/M3	N.E.
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	N.E.	N.E.	N.E.	N.E.
METHYL ETHYL KETOXIME	10 PPM	N.E.	N.E.	N.E.

PERSONAL PROTECTION:

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

SKIN PROTECTION:

USE GLOVES TO PREVENT PROLONGED SKIN CONTACT. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDRY BEFORE REUSE.

ENGINEERING MEASURES FOR COMBUSTIBLE DUST: NO INFORMATION

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: SOLVENT LIKE

ODOR THRESHOLD: N.E.

RELATIVE DENSITY: 0.933

PH: N.A.

FREEZE POINT, DEG. C: N.D.

VISCOSITY: N.D.

SOLUBILITY IN WATER: SLIGHT

PARTITION COEFFICIENT, N-OCTANOL/WATER: N.D.

DECOMPOSITION TEMP., DEG. C: N.D.

BOILING RANGE, DEG. C: -37 - 537

EXPLOSIVE LIMITS, VOL%: 0.7 - 13.0

FLAMMABILITY: SUPPORTS COMBUSTION

FLASH POINT, DEG. C: -96

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP., DEG. C: N.D.

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: N.D.

(SEE "OTHER INFORMATION" SECTION FOR ABBREVIATION LEGEND)

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F (49 DEG. C). AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. CONTAINS SOLVENTS WHICH MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

11. TOXICOLOGICAL INFORMATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES, SPRAY, VAPORS, OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION: HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS (DROWSINESS, DIZZINESS, NAUSEA, HEADACHES, PARALYSIS, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. CONTAINS TITANIUM DIOXIDE. TITANIUM DIOXIDE IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC. NO SIGNIFICANT EXPOSURE TO TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM DIOXIDE IS BOUND TO OTHER MATERIALS, SUCH AS IN PAINTS DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF TITANIUM DIOXIDE IN THE FORMULA.
(REF: IARC MONOGRAPH, VOL. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, INGESTION, INHALATION, SKIN ABSORPTION, SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
67-64-1	ACETONE	5800 MG/KG RAT	>15700 MG/KG RABBIT	50.1 MG/L
64742-48-9	NAPHTHA, HYDROTREATED HEAVY	>6000 MG/KG	>3160 MG/KG RAT	N.E. RABBIT
106-97-8	N-BUTANE	N.E.	N.E.	658 MG/L
13463-67-7	TITANIUM DIOXIDE	>10000 MG/KG RAT	2500 MG/KG	N.E.
6846-50-0	2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	>3200 MG/KG RAT	N.E.	>5.3 MG/L
96-29-7	METHYL ETHYL KETOXIME	930 MG/KG RAT	1100 MG/KG RABBIT	>4.83 MG/L RAT

N.E. - NOT ESTABLISHED

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

13. DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DO NOT INCINERATE CLOSED CONTAINERS. THIS PRODUCT AS SUPPLIED IS A USEPA DEFINED IGNITABLE HAZARDOUS WASTE. DISPOSE OF UNUSABLE PRODUCT AS A HAZARDOUS WASTE (D001) IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATION.

14. TRANSPORT INFORMATION

	DOMESTIC (USDOT)	INTERNATIONAL (IMDG)	AIR (IATA)	TDG (CANADA)
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT AND RELATED SPRAY PRODUCTS IN LTD QTY	AEROSOLS	AEROSOLS, FLAMMABLE	AEROSOLS
HAZARD CLASS	N.A.	2	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
GAS UNDER PRESSURE, CARCINOGENICITY, RESPIRATORY OR SKIN SENSITIZATION, SERIOUS EYE DAMAGE OR EYE IRRITATION, SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE), GERM CELL MUTAGENICITY

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:
NO SARA 313 COMPONENTS EXIST IN THIS PRODUCT.

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:
NO TSCA 12(B) COMPONENTS EXIST IN THIS PRODUCT.

U.S. STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

WARNING: CANCER AND REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.

16. OTHER INFORMATION

HMIS RATINGS:

HEALTH 2*
FLAMMABILITY 4
PHYSICAL HAZARD 0
PERSONAL PROTECTION X

NFPA RATINGS:

HEALTH 2
FLAMMABILITY 4
INSTABILITY 0

VOLATILE ORGANIC COMPOUNDS: 477 G/L

SDS REVISION DATE: 2/22/2019

REASON FOR REVISION:

REVISION DESCRIPTION CHANGED
PRODUCT COMPOSITION CHANGED

SUBSTANCE AND/OR PRODUCT PROPERTIES CHANGED IN SECTION(S):

- 02 - HAZARD IDENTIFICATION
- 09 - PHYSICAL & CHEMICAL PROPERTIES
- 14 - TRANSPORT INFORMATION
- 15 - REGULATORY INFORMATION
- 16 - OTHER INFORMATION

REVISION STATEMENT(S) CHANGED

LEGEND:

N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
N.D. - NOT DETERMINED

RUST-OLEUM CORPORATION BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.