



PNT107

SCHOOLS

215 S.E. 6th Ave.
LSBORO, OR 97123

MATERIAL SAFETY DATA SHEET

IN 0028

SECTION I

PRODUCT CODE NUMBER: _____ *TLV: _____
MANUFACTURER'S NAME: Illinois Bronze Paint Company EMERGENCY INFORMATION: (312) 359-6453
MANUFACTURER'S ADDRESS: 300 E. Main Street, Lake Zurich, IL 60047
PRODUCT: Fiesta (all colors), Spray Paint COMMON NAME: _____
GENERIC NAME: _____ CHEMICAL NAME: _____
CHEMICAL FAMILY: _____ DOT PROPER SHIPPING NAME: _____
WARNING STATEMENTS: _____

SECTION II - INGREDIENTS

	C.A.S. #	Vapor Pressure	%	Occupational Exposure Limit	TLV
Mineral Spirits		4 mm	0-4	500 ppm	
Toluol		17 mm	0-30	100 ppm	
M&P Naphtha		17 mm	0-15	500 ppm	
Methylene Chloride		350 mm	30-48	250 ppm	
Propellant (Propane-Isobutane)		4400 mm	30-35	N/A	
Inert Resins & Pigments		N/A	Balance	N/A	

* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: 104 - 300°F VAPOR PRESSURE: _____
VAPOR DENSITY: Heavier than air. SOLUBILITY IN WATER: _____
SPECIFIC GRAVITY: _____ PERCENT VOLATILE: 90%
EVAPORATION RATE: Faster than ether (Propellant) Slower than ether (Solvent) APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: -40C (-40F) Limits: LEL: 0.8% EXTINGUISHING MEDIA: Foam, CO₂, Dry Chemical
FIRE FIGHTING PROCEDURES: _____ DOT FLAMMABILITY: OSHA Flammable Liquid - Class IA
CLASSIFICATION: DOT Flammable Liquid
Cans will rupture from internal pressure at about 190°F and discharge flammable contents. When heated to
UNUSUAL FIRE AND EXPLOSION HAZARDS: decomposition, toxic fumes are formed.

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.
SKIN CONTACT: Wipe off with towel. Remove remainder with mineral spirits, turpentine, or lacquer thinner. Wash with soap and water. Remove contaminated clothing.
INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.
INGESTION: _____

Incompatible With: Not given
Hazardous Decomposition Products: Not given
Hazardous Polymerization: Will not occur.
Conditions To Avoid: N/A

SECTION VII. SPILL OR LEAK PROCEDURES

Procedures In Case of Spill or Leak: Treat like oil or petroleum solvent.
Waste Disposal: Forced combustion or with other petroleum products.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Type of Respiratory Protection: Avoid prolonged inhalation of concentrated vapors.
Ventilation: Adequate ventilation (local exhaust).
Protective Gloves: N/A
Eye Protection: Do not splash in eye.
Other Protective Equipment: N/A

SECTION IX. SPECIAL PRECAUTIONS

Handling/Storage Precautions: Do not store near heat source. Flammable.
Other Precautions: N/A