



PNT197

SCHOOLS

215 S.E. 8th Ave.
LEBORO, OR 97123

MATERIAL SAFETY DATA SHEET

CM 0070

SECTION I

PRODUCT CODE NUMBER _____ *TLV _____
MANUFACTURER'S NAME Jasco Chemical Company EMERGENCY INFORMATION: (415) 968-6005
MANUFACTURER'S ADDRESS 1710 Villa Street, Mountain View, CA 94042
PRODUCT: Laquer Thinner COMMON NAME: _____
GENERIC NAME _____ CHEMICAL NAME: _____
CHEMICAL FAMILY: Solvents DOT PROPER SHIPPING NAME: _____
WARNING STATEMENTS: _____

SECTION II - INGREDIENTS

Paints, Preservatives and Solvents:	C.A.S. #	%	TLV
Solvents		100	
Contains hydrocarbon and oxygenated solvents			
Glycol Ether EB		2	50

* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: 760 mm Hg: 133-340 VAPOR PRESSURE: _____
VAPOR DENSITY: >2 SOLUBILITY IN WATER: 35-40%
SPECIFIC GRAVITY: 0.8 PERCENT VOLATILE: by volume: 100%
EVAPORATION RATE: >2 APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: 10-14°F T.O.C. estimated °F C.C. _____
EXTINGUISHING MEDIA: Exclude air. Use Foam, carbon diox Dry Chemical
FIRE FIGHTING PROCEDURES: Water should not be used DOT FLAMMABILITY
except as a fog. CLASSIFICATION: _____
UNUSUAL FIRE AND EXPLOSION HAZARDS: _____

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Seek medical advice if irritation persists. Flush with water.
SKIN CONTACT: Flush with water. Seek medical advice if conditions persists.
INHALATION: Remove to fresh air. Restore breathing if required. Call a physician.
INGESTION: Do not induce vomiting. See medical advice if condition persist.

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS THRESHOLD LIMIT VALUE: 200 ppm (Calculated). EFFECTS OF OVEREXPOSURE: Breathing vapor may irritate nose and throat. May cause nausea, dizziness.

CHRONIC EFFECTS _____

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable. Heat and fires.

INCOMPATIBILITY (Materials to Avoid): Strong alkalis or strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: _____

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Eliminate all sources of ignition. Flush with water to a tank or well ventilated area.

WASTE DISPOSAL METHOD: Incinerate if permitted, or bury in a sanitary fill. Dispose in conformance with local regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: All-purpose canister mask or air-supplied mask if TLV exceeded.

VENTILATION: Good. LOCAL EXHAUST: Use in ventilated areas.

PROTECTIVE GLOVES: Advisable.

EYE PROTECTION Eye goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: _____

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: CAUTION: Extremely flammable.

OTHER PRECAUTIONS: Avoid repeated contact with skin.

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: _____