



SECTION I

PRODUCT CODE NUMBER Cl *TLV _____
MANUFACTURER'S NAME Westwood Ceramic Supply Company EMERGENCY INFORMATION (818) 330-0631
MANUFACTURER'S ADDRESS 14400 Lomitas Avenue, City of Industry, CA 91746
PRODUCT Clays COMMON NAME WCS Clays
GENERIC NAME _____ CHEMICAL NAME _____
CHEMICAL FAMILY Ceramic Clays DOT PROPER SHIPPING NAME _____
WARNING STATEMENTS _____

SECTION II - INGREDIENTS

C.A.S. #	%	TLV
Paints, Preservatives & Solvents: None.		
Alloys and Metallic Coating: None.		
Hazardous Mixtures of other liquids, solids, or gases: A clay body is a blend of naturally occurring minerals and may contain 5—30% total silica. The TLV for free or crystalline silica is 10mg/m ³ /% Respirable Quartz +2.		

* Threshold limit value set by (A) OSHA, (B) ACGIH, (C) See Section III, (D) Other, (NE) Not Established [Units are in PPM unless otherwise specified]

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE: Not Available VAPOR PRESSURE: Not Available
VAPOR DENSITY: Not Available SOLUBILITY IN WATER: Negligible
SPECIFIC GRAVITY: 2.6 — 2.75 PERCENT VOLATILE: Not Available
EVAPORATION RATE: Not Available APPROXIMATE BULK DENSITY _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE: None. EXTINGUISHING MEDIA: None.
FIRE FIGHTING PROCEDURES: None. DOT FLAMMABILITY CLASSIFICATION: _____
UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Rinse eyes with generous amounts of water.
SKIN CONTACT: Wash with soap and water.
INHALATION: Remove to fresh air, contact physician.
INGESTION: _____

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS THRESHOLD LIMIT VALUE: Silica TLV = 10 mg/m³/ % Respirable Quartz +2. EFFECTS OF OVEREXPOSURE:
Avoid breathing dust and keep dust out of eyes.

CHRONIC EFFECTS _____

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable.

INCOMPATIBILITY (Materials to Avoid): _____

HAZARDOUS DECOMPOSITION PRODUCTS _____

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Normal clean up procedures. Care should be taken to avoid causing dust to become airborne. Vacuum cleaning systems are recommended.

WASTE DISPOSAL METHOD: This product is a blend of naturally occurring minerals and may be considered non hazardous waste. Must be made in accordance with federal, state, and local regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: When dust is present wear NIOSH approved mask.

VENTILATION: Exhaust to outside.

PROTECTIVE GLOVES: Recommended to sensitive skin.

EYE PROTECTION: _____

OTHER PROTECTIVE EQUIPMENT: None.

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Controls should be used to maintain "free" silica dust exposures below the TLV.

OTHER PRECAUTIONS: _____

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: _____