



SCM CORPORATION

GLI COATINGS & RESINS DIVISION
925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO 12161 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

21208

PAGE 1

SECTION I

CODE IDENTIFICATION 21208 DATE PRINTED 02/28/86
PRODUCT IDENTIFICATION LATEX TRAFFIC PAINT - WHITE

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	WEIGHT PERCENT	THRESHOLD LIMIT VALUE	LEL	VAPOR PRESS.
CALCIUM CARBONATE CAS NO. - 1317-65-3	35	10 MG/M3		
TITANIUM DIOXIDE CAS NO. - 1317-80-2	8	10 MG/M3		
SiO ₂ CAS NO. - 14808-60-7	8	0.1 MG/M3		
ETHYLENE GLYCOL CAS NO. - 107-21-1	2	C 50 PPM	3.2	.10
ESTER ALCOHOL CAS NO. - 25265-77-4	1		.6	1.00
FREE FORMALDEHYDE CAS NO. - 50-00-0	.5	C 2 PPM		

C-CEILING - THE CONCENTRATION THAT SHOULD NOT BE EXCEEDED EVEN INSTANTANEOUSLY.

THE THRESHOLD LIMIT VALUE (TLV) IS THE TIME WEIGHTED AVERAGE (TWA) TO WHICH IT IS BELIEVED THAT MOST WORKERS MAY BE EXPOSED 8-10 HOURS PER DAY, 40 HOURS PER WEEK WITHOUT ADVERSE HEALTH EFFECTS.

LEL - THE LOWER EXPLOSIVE LIMIT IS THE LOWEST CONCENTRATION (% OF VOLATILES IN AIR) THAT WILL PRODUCE A FLASH OF FIRE WHEN AN IGNITION SOURCE IS PRESENT.

MATERIAL SAFETY DATA SHEET

1210



SCM CORPORATION

GLASS COATINGS & RESINS DIVISION
925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information or of any product, method or apparatus mentioned and must make your own determination of its suitability and completeness for your own use, for the protection of the environment and the health and safety of your employees and users of this material.

21208

PAGE 2

SECTION III - PHYSICAL DATA

BOILING RANGE 356 - 395 F WEIGHT PER GALLON 12.80
% VOLATILE BY VOLUME 53.50

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (SETA) ABOVE 200 F LOWER EXPLOSIVE LIMIT .6
DOT (PSN) PAINT
HAZARD CLASS NOT RESTRICTED
EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

SECTION V - HEALTH HAZARD DATA

ROUTE OF ENTRY INHALATION
SKIN
EYES
INGESTION

EFFECTS OF OVEREXPOSURE

IRRITATION OF EYES, SKIN, RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO DIZZINESS AND/OR LIGHTHEADEDNESS. POSSIBLE NAUSEA, VOMITING, DIGESTIVE SYSTEM PROBLEMS, DIFFICULTY OF BREATHING. CONTAINS FORMALDEHYDE. FORMALDEHYDE SHOULD BE HANDLED AS A POTENTIAL OCCUPATIONAL CARCINOGEN OSHA/NIOSH (1981).

MATERIAL SAFETY DATA SHEET

1210



SCM CORPORATION

GLIDCOAT COATINGS & RESINS DIVISION
925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use for the protection of the environment, and the health and safety of your employees and users of this material.

21208

PAGE 3

SECTION V - HEALTH HAZARD DATA

EMERGENCY AND FIRST AID PROCEDURES

INHALATION MOVE PERSON TO WELL VENTILATED AREA.
GET EMERGENCY MEDICAL ATTENTION.
ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.

SKIN CONTACT FLUSH FROM SKIN WITH WATER, THEN WASH THOROUGHLY WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET EMERGENCY MEDICAL ATTENTION.

INGESTION GET EMERGENCY MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

STABILITY STABLE

INCOMPATIBILITY OXIDIZERS

CONDITIONS TO AVOID
ELEVATED TEMPERATURES
CONTACT WITH OXIDIZING AGENT

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE
CARBON DIOXIDE

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

MATERIAL SAFETY DATA SHEET

1210



SCM CORPORATION

GLUE, IN COATINGS & RESINS DIVISION
925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 626-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

21208

PAGE 4

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION.
VENTILATE AREA.
SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.
AVOID DISCHARGE TO NATURAL WATERS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

VENTILATION PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH
SAFETY SHOWER
SAFETY GLASSES OR GOGGLES
IMPERVIOUS GLOVES

SECTION IX - SPECIAL PRECAUTIONS

HANDLING AND STORAGE

STORE BELOW 100 F.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION.
DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS.
WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.
AVOID BREATHING SANDING DUST.