HENKEL CONSUMER ADHESIVES

04/21/03

AVON, OH 44011 TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page

Page 01 of 05

ACE ALL-PURPOSE CONTACT CEMENT 50-08866

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	ACE ALL-PURPOSE CONTACT CEMENT
Item No.:	50-08866
Part No.:	
Product Type:	Contact Cement

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS No.	00
CYCLOHEXANE*	110-82-7	40-60
METHYL ETHYL KETONE*	78-93-3	10-20
Neoprene	9010-98-4	10-20
n-PROPYL ACETATE	109-60-4	5-10
Proprietary Resin Compound	Proprietary	5-10
Rosin	068083-03-4	1-5

* This component is listed as a SARA Section 313 Toxic Chemical.

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
CYCLOHEXANE	300 ppm TWA 1030 mg/m3	300 ppm TWA 1030 mg/m3	None
METHYL ETHYL KETONE	200 ppm TWA 590 mg/m3	200 ppm TWA 590 mg/m3	None
n-PROPYL ACETATE	200 ppm TWA 835 mg/m3	200 ppm TWA 840 mg/m3	None
Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)	
METHYL ETHYL KETONE	300 ppm 885 mg/m3	300 ppm 885 mg/m3	
n-PROPYL ACETATE	250 ppm 1040 mg/m3	250 ppm 1050 mg/m3	

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory tract irritation. May cause drying or defatting of skin leading to dermatitis. Inhalation of vapors may cause central nervous effects including dizziness, weakness, nausea, and headache. Ingestion may cause irritation, nausea, vomiting and diarrhea.

04/21/03 HENKEL CONSUMER ADHESIVES AVON, OH 44011 TELEPHONE: (440) 937-7000 MATERIAL SAFETY DATA SHEET Page 02 of 05 Product Name: ACE ALL-PURPOSE CONTACT CEMENT Item No.: 50-08866 3. HAZARDS IDENTIFICATION (continued) Overexposure to methyl ethyl ketone may cause lung, kidney and liver damage. Primary Routes of Entry: Skin, eye, inhalation, ingestion Signs and Symptoms Eye, skin, and respiratory tract irritation. of Exposure: Dizziness, weakness, headaches and nausea. Existing Conditions Aggravated by Exposure: Skin disorders Literature Referenced Carcinogen Ingredients Target Organ and Other Health Effects NTP IARC OSHA CYCLOHEXANE CNS IRR NO NO NO METHYL ETHYL KETONE NO N/A NO CNS IRR NTO NO N/A NO Neoprene n-PROPYL ACETATE CNS IRR NO NO NO Proprietary Resin Compound No Data NO NO NO Rosin No Data NO NO NO _____ Abbreviations N/A Not Applicable CNS Central nervous system IRR Irritant NTO No Target Organs 4. FIRST AID MEASURES Do NOT induce vomiting unless directed to do so by a Ingestion: physician. Never give anything by the mouth to an unconscious person. Get medical attention immediately. Remove to fresh air. If Inhalation: breathing is difficult, administer oxygen. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. Skin Contact: Remove contaminated clothing, wash immediately with soap and water. Wash contaminated clothing thoroughly before reuse. If irritation persists, obtain medical attention. Eye Contact: Flush thoroughly with water for at least 15 minutes. If irritation persists, obtain medical attention. 5. FIRE FIGHTING MEASURES < 0°F Flash Point:

Recommended Extinguishing Agents: Water fog, carbon dioxide, foam, or dry chemical. Special Firefighting Procedures: Water spray can be used to cool containers. A solid

04/21/03 HENKEL CONSUMER ADHESIVES AVON, OH 44011 TELEPHONE: (440) 937-7000 MATERIAL SAFETY DATA SHEET Page 03 of 05 Product Name: ACE ALL-PURPOSE CONTACT CEMENT Item No.: 50-08866 5. FIRE FIGHTING MEASURES (continued) stream of water directed on hot and/or burning material may cause violent frothing. Hazardous Products formed by Fire or Thermal Decomp Oxides of carbon, hydrocarbons, chlorine compounds. Unusual Fire or Explosion Hazards: None Explosive Limits: (% by volume in air)Lower Not available (% by volume in air)Upper Not available 6. ACCIDENTAL RELEASE MEASURES Steps to be taken in case Eliminate all sources of ignition. Ventilate area. of spill or leak: Clean up spills immediately. Soak up with an inert absorbent. Clean residual material with soap and water. Placed in a closed container until disposal. 7. HANDLING AND STORAGE Safe Storage: Keep in a cool and well ventilated area. Keep container closed tightly closed and sealed until ready to use. (Contact Loctite Customer Service 1-800-243-4874 for shelf life information) Handling: Keep away from heat, sparks, and flame. Keep container closed. Use only with adequate ventilation. 8. EXPOSURE CONTROLS, PERSONAL PROTECTION Eyes: Chemical splash goggles or safety glasses with side shields. Skin: Use chemical resistant, impermeable gloves. Ventilation: Use local exhaust ventilation to maintain airborne exposure levels below established exposure limits. Respiratory Use NIOSH approved respirator as required to prevent overexposure. See Section 2 for Exposure Limits. 9. PHYSICAL AND CHEMICAL PROPERTIES Appearance: Yellowish Liquid Odor: Solvent Boiling Point: More than 300°F Does not apply pH: Solubility in Water: Insoluble Specific Gravity 0.827 Volatile Organic Compound

(EPA Method 24) Not available

Not available

Vapor Pressure:

HENKEL CONSUMER ADHESIVES 04/21/03 AVON, OH 44011 TELEPHONE: (440) 937-7000 MATERIAL SAFETY DATA SHEET Page 04 of 05 Product Name: ACE ALL-PURPOSE CONTACT CEMENT Item No.: 50-08866 9. PHYSICAL AND CHEMICAL PROPERTIES (continued) Vapor Density: Not available Evaporation Rate (Ether = 1)More than butyl acetate 10. STABILITY AND REACTIVITY Stability: Stable Hazardous Polymerization: Will not occur Incompatibility: Strong oxidizing agents. Conditions to Avoid: Keep away from heat, spark and flame. Hazardous Decomposition Products (non-thermal): None 11. TOXICOLOGICAL INFORMATION See Section 3. 12. ECOLOGICAL INFORMATION No data available 13. DISPOSAL CONSIDERATIONS Recommended methods of disposal: Dispose of following EPA and local regulations. Use of an approved hazardous waste disposal contractor is recommended. EPA Hazardous Waste Number D001/D035 - Hazardous waste per 40CFR 261.21 and a TCLP waste per 261.24/Methyl Ethyl Ketone. 14. TRANSPORTATION INFORMATION DOT (49 CFR 172) Domestic Ground Transport Proper Shipping Name: Consumer Commodity (Not more than one liter); Adhesives, containing a flammable liquid (More than one liter) Hazard Class or Division: ORM-D (Not more than one liter); Class 3, Packing Group II (More than one liter) Identification Number: None (Not more than one liter); UN 1133 (More than one liter) Marine Pollutant: None IATA Proper Shipping Name: Consumer Commodity (Not more than 500 ml); Adhesives, containing a flammable liquid (More than 500 m1) Class or Division: Class 9 (Not more than 500 ml);

HENKEL CONSUMER ADHESIVES 04/21/03 AVON, OH 44011 TELEPHONE: (440) 937-7000 MATERIAL SAFETY DATA SHEET Page 05 of 05 Product Name: ACE ALL-PURPOSE CONTACT CEMENT Item No.: 50-08866 14. TRANSPORTATION INFORMATION (continued) Class 3, Packing Group II (More than 500 ml) ID 8000 (Not more than 500 ml); UN or ID Number: UN 1133 (More than 500 ml) 15. REGULATORY INFORMATION CA Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer. 16. OTHER INFORMATION Estimated NFPA(R) Code: 2 Health Hazard: Fire Hazard: 3 Reactivity Hazard: 0 Specific Hazard: Does not apply Estimated HMIS(R) Code: 2* Health Hazard: Flammability Hazard: 3 0 Reactivity Hazards: Personal Protection: See Section 8. NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn. (24hr.) Phone: (440) 937-7000