



PNT097

SCHOOLS

715 S.E. 8th Ave.
ILLSBORO, OR 97123

MATERIAL SAFETY DATA SHEET

IN 0026

SECTION I

PRODUCT CODE NUMBER _____ TLV _____
MANUFACTURER'S NAME Reckitt Chemicals, Inc. EMERGENCY INFORMATION (714) 946-3871
MANUFACTURER'S ADDRESS 430 S. 11th Avenue, Ukiah, CA 91786
PRODUCT Everyday Spray Paint-Gold COMMON NAME _____
GENERIC NAME _____ CHEMICAL NAME _____
CHEMICAL FAMILY _____ DOT PROPER SHIPPING NAME _____
WARNING STATEMENTS _____

SECTION II - INGREDIENTS

	C.A.S. #	%	TLV
Aliphatic Hydrocarbons	64742-89-8	7-8	300
Acetone	67-64-1	8-9	750
Xylene	1330-20-7	27-28	100
Cyclohexane	110-82-7	16-17	300

* Threshold limit value set by (A) OSHA, (B) ACGIH (C) See Section III, (D) Other, (NE) Not Established (Units are in PPM unless otherwise specified)

SECTION III - PHYSICAL DATA

APPROXIMATE BOILING RANGE _____ VAPOR PRESSURE _____
VAPOR DENSITY Heavier than air. SOLUBILITY IN WATER _____
SPECIFIC GRAVITY _____ PERCENT VOLATILE _____
EVAPORATION RATE Slower than Ether APPROXIMATE BULK DENSITY: _____

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT RANGE -40°F EXTINGUISHING MEDIA Carbon Dioxide, Dry Chem, Alcohol
Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
FIRE FIGHTING PROCEDURES See on attached sheet. DOT FLAMMABILITY CLASSIFICATION EXTREMELY FLAMMABLE
UNUSUAL FIRE AND EXPLOSION HAZARDS _____

SECTION V - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: _____

SKIN CONTACT: _____

INHALATION: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
INGESTION: Do not induce vomiting, keep person warm, quiet and get medical attention. Aspiration of material into lungs due to vomiting can cause chemical pneumonitis which can be fatal.

SECTION VI - PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

ACUTE EFFECTS: Inhalation is anesthetic. Irritation of respiratory tract or nervous system depression.
Headache, dizziness, nausea, confusion, unconsciousness or coma. Skin or eye irritation: Primary irritation.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Reports have associated repeated and
 CHRONIC EFFECTS: prolonged occupational overexposure to solvents with permanent brain and nervous system
damage. Routes of Entry are dermal and inhalation.

SECTION VII - REACTIVITY DATA

STABILITY (Conditions to Avoid): Stable.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon monoxide (as during a fire).

HAZARDOUS POLYMERIZATION (Conditions to Avoid): Will not occur.

SECTION VIII - SPILL OR LEAK PROCEDURES

PROCEDURES IN CASE OF RELEASE OR SPILL: Remove all sources of ignition, flames, hot surfaces and electrical static
or fractional spark. Avoid breathing vapors; ventilate area. Remove
with inert absorbent and nonsparking tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If eye watering, headache or dizziness is experienced, increase fresh air, or wear
respiratory equipment (NIOSH/MSHA LC 23C or equivalent) or leave the area.

VENTILATION: Do not flameout, blaze or weld coated parts without respiratory protection. Provide general or
diluting ventilation sufficient to keep vapor concentration below TLV and LEL.

PROTECTIVE GLOVES: Rubber

EYE PROTECTION: Safety glasses with splash shields or splash goggles.

OTHER PROTECTIVE EQUIPMENT: Prevent prolonged skin contact with contaminated clothing. Remove and wash contaminated
clothing. Discard contaminated shoes.

SECTION X - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS: Do not store in temperatures above 120°F. Store large quantities in building
designated and protected for storage of N.F.P.A. Class IA Flammable Liquids.

OTHER PRECAUTIONS: Do not use near open flame. Do not take internally. Close container after each use.
Avoid breathing vapors. Keep out of reach of children. Containers should be grounded when pouring.

SECTION XI - DOCUMENTARY INFORMATION

PRODUCT CODE NUMBER: _____

ISSUE DATE: _____

REPLACES MSDS NUMBER: _____

PREVIOUS PRODUCT CODE NUMBER: _____

PREVIOUSLY ISSUED: March 11, 1985